

Eliminate PC2201

ELIMINATE is a technology-based aircraft lavatory care and ongoing maintenance system. **ELIMINATE'S** toilet additive is specifically designed to break up and disperse all hard to remove residues, mineral scale, and waste by-products. It is formulated to be safe to equipment while dislodging and breaking down lavatory sludge within the system.

APPLICATION

Empty lavatory holding tank, and add **ELIMINATE** (full strength is recommended for first use). Allow to soak during routine overnight service. Flush all toilet compartments several times during process to ensure that pumps and flush rings are saturated.

Nuvite's Recommended Maintenance and Servicing Process:

- 1. With **RID**, wipe down internal/external shrouds, flooring, cabinetry, and sidewalls.
- 2. Fill the lavatory tank with **ELIMINATE** (1:4 mixture) to flush ring (top of toilet).
- 3. Allow to soak for 6-8 hours.
- 4. Flush the lavatory hourly (1-2x) to distribute **ELIMINATE** throughout the system.
- 5. After the soak period, flush out the tank thoroughly.
- 6. Refill with Nuvite's **GOODBYE NF** to deodorize during flight.
- 7. We recommend performing this procedure on a 30-day cycle.
- 8. Use **POWERPAX** for odor control on quick turns, sitting aircraft, or for a full-service.

For best results, please consult with UPI/Nuvite technical staff for further recommendations, and application techniques.

BENEFITS

- Exceptional dispersing and cleaning performance
- Safe to internal pumps, airport tritcherator and municipal standards
- Conforms to airframe OEM standards and specifications

PHYSICAL CHARACTERISTICS

Test	Eliminate
Specific Gravity	1.02
Appearance	Dark Brown Liquid
рН	11.8 - 12.5

AVAILABILITY

1 Gallon(s), 5 Gallon(s), 55 Gallon(s), 1 Quart(s), 275 Gallon Tote

The Science of Surfacing* | 85 Jetson Lane | Central Islip, NY 11722 | 516.935.4000 | Universalphotonics.com