



CitriCut Gel

HEAVY-DUTY CITRUS-BASED WETWASH & DEGREASER

For heavy duty cleaning of gears, wheel wells, flaps cowling & more

WETWASH

1. Dilute **CitriCut Gel** 1:4 to 1:8* with water.
2. Apply **CitriCut Gel** to aircraft surfaces by spray or mop.
3. Agitate to loosen soil.
4. DO NOT allow soaked area to completely dry.
5. Rinse with water.

DEGREASING

1. Use **CitriCut Gel** full strength or dilute up to 1:4* with water.
2. Apply **CitriCut Gel** to surface manually with mophead/pad.
3. Allow to soak 5-10 minutes.
4. DO NOT allow soaked area to completely dry.
5. Rinse with high-pressure water.

HEAVY DUTY CLEANING

1. Use **CitriCut Gel** full strength – DO NOT DILUTE.
2. Apply **CitriCut Gel** to surface manually with mophead/pad.
3. Allow to soak 5-10 minutes.
4. DO NOT allow soaked area to completely dry.
5. Rinse with high-pressure water.

VERTICAL OR OVER HEAD SURFACES

1. Use **CitriCut Gel** full strength – DO NOT DILUTE.
2. Spray **CitriCut Gel** onto surface with low-pressure spray.
3. Allow to soak 5-10 minutes.
4. Agitate to loosen soil.
5. DO NOT allow soaked area to completely dry.
6. Rinse with high-pressure water.

**Product dilutions are determined by extent, condition & soil type.*

When using any NUVITE product, please refer to appropriate procedures and recommendations for use and equipment, or contact a NUVITE technician for more information, unique applications and special requirements.

QUESTIONS? NUVITE technicians have the answers 800.394.8351

