



## CitriCut Gel

### **HEAVY-DUTY CITRUS-BASED WETWASH & DEGREASER**

For heavy duty cleaning of gears, wheel wells, flaps cowling & more



#### **WETWASH**

1. Dilute **CitriCut Gel** 1:4 to 1:8\* with water.
2. Apply **CitriCut Gel** to aircraft surfaces by spray or mop.
3. Agitate to loosen soil.
4. DO NOT allow soaked area to completely dry.
5. Rinse with water.

#### **DEGREASING**

1. Use **CitriCut Gel** full strength or dilute up to 1:4\* with water.
2. Apply **CitriCut Gel** to surface manually with mophead/pad.
3. Allow to soak 5-10 minutes.
4. DO NOT allow soaked area to completely dry.
5. Rinse with high-pressure water.

#### **HEAVY DUTY CLEANING**

1. Use **CitriCut Gel** full strength – DO NOT DILUTE.
2. Apply **CitriCut Gel** to surface manually with mophead/pad.
3. Allow to soak 5-10 minutes.
4. DO NOT allow soaked area to completely dry.
5. Rinse with high-pressure water.

#### **VERTICAL OR OVER HEAD SURFACES**

1. Use **CitriCut Gel** full strength – DO NOT DILUTE.
2. Spray **CitriCut Gel** onto surface with low-pressure spray.
3. Allow to soak 5-10 minutes.
4. Agitate to loosen soil.
5. DO NOT allow soaked area to completely dry.
6. Rinse with high-pressure water.

*\*Product dilutions are determined by extent, condition & soil type.*

*When using any NUVITE product, please refer to appropriate procedures and recommendations for use and equipment, or contact a NUVITE technician for more information, unique applications and special requirements.*

QUESTIONS? NUVITE technicians have the answers 800.394.8351