



## CitriCut Xtra

### **CITRUS-BASED CLEANER FOR WETWASH, DRYWASH, & CHEMWIPE**

For periodic cleaning to enhance gloss factors while providing a protective sealant



### **WETWASH**

1. Dilute **CitriCut Xtra** 1:12 to 1:20\* with water.
2. Apply to surfaces manually with mophead/pad or by approved portable sprayer.
3. Agitate painted surface to loosen soils.
4. Wipe dry with a clean terry towel or string mop.
5. Allow **CitriCut Xtra** sealant to dry.

### **DRYWASH**

1. Dilute **CitriCut Xtra** 1:8 to 1:12\* with water.
2. Apply to aircraft surfaces manually with mophead/pad.
3. Agitate painted surface to loosen soils.
4. Wipe dry with a clean terry towel or string mop.
5. Allow **CitriCut Xtra** sealant to dry.

### **HEAVY-DUTY CLEANING**

1. Use **CitriCut Xtra** full strength or dilute up to 1:4\* with water.
2. Apply to aircraft surfaces manually with mophead/pad.
3. Agitate painted surface to loosen soils.
4. Wipe dry with a clean terry towel or string mop.
5. Allow **CitriCut Xtra** sealant to dry.

### **CHEMWIPE (HANDWASH/WAX)**

1. Use **CitriCut Xtra** full strength or dilute up to 1:4\* with water.
2. Apply to aircraft surfaces manually with mophead/pad.
3. Agitate surface with a wash pad to loosen soils.
4. DO NOT allow work surface area to dry.
5. Hand buff painted surface until dry with clean dry mop head or terry cloth pad.

*\*Product dilutions are determined by extent, condition & soil type.*

*When using any NUVITE product, please refer to appropriate procedures and recommendations for use and equipment, or contact a NUVITE technician for more information, unique applications and special requirements.*

QUESTIONS? NUVITE technicians have the answers 800.394.8351