

# CITRICUT GEL

PC2299 Series



**CITRICUT GEL** is a citrus based wetwash used to clean heavy build-up soil conditions on wheel wells and flap wells. It is specially designed to cling to vertical and overhead surfaces while providing increased wet-out time and penetrating stubborn dirt or caked-on grease.

## APPLICATION

**Normal Cleaning:** Dilute **CITRICUT GEL** 1:2 – 1:8 with water. Apply to aircraft surfaces by spray or mop application. Allow to soak long enough to loosen surface dirt. Agitate to loosen soil and rinse with water.

**Heavy-Duty Cleaning:** Use **CITRICUT GEL** undiluted. Allow to soak approximately 5-15 minutes without allowing to completely dry. Rinse with water using pressure washer under 80 PSI.

**Vertical or overhead surfaces:** Spray **CITRICUT GEL** undiluted with low pressure spray on surface. Allow to soak without drying. Agitate to loosen and spray rinse with pressure water.

For best results, please consult with UPI/Nuvite technical staff for further recommendations, and application techniques.

## BENEFITS

- Heavy-duty cleaner and degreaser in gel form that clings to vertical and overhead surfaces
- Effective for cleaning multiple soil conditions such as dirt, carbon, grease, and lubricants
- Environmentally friendly and safe for operator use
- Conforms to airframe OEM standards and specifications

## PHYSICAL CHARACTERISTICS

TEST	CITRICUT GEL
Appearance	Orange semi viscous liquid
pH	11.8 - 12.5
Specific gravity	1.02

## AVAILABILITY

275 Gallon, 55 Gallon, 5 Gallon, 1 Gallon, 1 Quart