

NUGEAR SC

PC2209 Series



NUGEAR SC is a heavy duty aqueous cleaning compound for exterior aircraft engine and component degreasing applications. **NUGEAR SC** is used as a wet wash or in a hot immersion tank and spray cabinet application.

APPLICATION

Normal – Hand Cleaning: Dilute **NUGEAR SC** 1:4 – 1:10 with water. Apply to surface by mop or spray method. Agitate to loosen soil followed by water rinse and dry with terry towel.

General Component Part Cleaning: Dilute according to soil condition and immerse in tank or basket under ambient or hot temperature method or in ultrasonic equipment.

Engine Component Cleaning – Hot immersion tank: Dilute **NUGEAR SC** 1:4 for use in tank applications at 140°F (60°C). Follow OEM manufacturer's Maintenance Manual procedures and requirements.

For best results, please consult with UPI/Nuvite technical staff for further recommendations, and application techniques.

BENEFITS

- Superior wetting and soil penetration
- Conforms to Airframe OEM standards and specifications
- Rolls Royce, General Electric, and Pratt & Whitney SPMC 151, PMC 5404, and PMC 1481 approved

PHYSICAL CHARACTERISTICS

TEST	NUGEAR SC
Appearance	Yellow Liquid
pH	11.8 - 12.5
Specific gravity	1.01
Solubility in water	Infinite

AVAILABILITY

55 Gallon, 5 Gallon, 1 Gallon, 1 Quart