

SS 9-3

PC2161 Series



SS 9-3 is an alkaline all-purpose liquid cleaning compound for exterior aircraft wetwashing. SS 9-3 is designed to clean the toughest of grease, oils, and fluid leakage. SS 9-3 can also be diluted to make an easy-to-use debugger and whole-frame wipe-down fluid that leaves a clean shiny surface.

APPLICATION

Normal Soil, Hand wipe down or debugging: Prepare SS 9-3 1:12 – 1:15 with water. Use trigger spray bottle and lightly spray area. Use a soft terry towel to wipe surface. Buff with a dry clean towel to shine.

Wetwash: Dilute SS 9-3 1:12 – 1:20 in water. Apply to surface by spray or mop, agitate to loosen soil, remove with water spray.

Heavily Soiled: Spray undiluted SS 9-3, or mix 1:2 depending upon conditions. Allow to sit approximately 15-20 minutes without drying, and rinse with water or pressure spray.

For best results, please consult with UPI/Nuvite technical staff for further recommendations, and application techniques.

BENEFITS

- Usable as hand debugger and full frame wipe down fluid
- Safe to all component parts and exterior finishes
- May be used as a general purpose cleaner for automotive interiors
- Conforms to airframe OEM standards and specifications

PHYSICAL CHARACTERISTICS

TEST	SS 9-3
Appearance	Clear to amber liquid
pH	11.8 - 12.5
Specific gravity	1.03

AVAILABILITY

55 Gallon, 5 Gallon, 1 Gallon, 1 Quart